Datasheet and description



Avide LED Flood Light Slim 10W CW 6400K

Product code: ABSFLCW-10W

Brand link: avidelighting.com/qr/ABSFLCW-10W

ID: AB-190518

Company name: Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-11-15

Page: 1/3

SPECIFICATIONS

EAN code: 5999097914220

Warranty: 3year(s)
Working temperature: -20 - +40 °C
Packaging: $1/b \ 30/c \ 1320/p$

Certifications: CE

TECHNICAL DETAILS

Wattage: 10W

Voltage: 85-265V

Beam angle: 120°

Dimmability: No

Lumen output: 910lm

Color temperature: 6 400K

Lifetime: 30 000h

Energy class: G
Type of LED: COB

Driver:

CRI: >80
IP standard: IP65

BOX PICTURE



Datasheet and description



Avide LED Flood Light Slim 10W CW 6400K

Product code: ABSFLCW-10W

Brand link: avidelighting.com/qr/ABSFLCW-10W

ID: AB-190518

Company name: Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-11-15

Page: 2/3

PRODUCT SIZE

Width: 115mm
Height: 135mm
Depth: 40mm

CARDBOARD BOX

EAN: 5999097914220 Packaging: 1/b 30/c 1320/p

Dimensions: 120mm x 41mm x 140mm

Net weight: 425.9g Gross weight: 440g

PRODUCT PICTURE




CARTON

EAN: 5999097914237 Packaging: 1/b 30/c 1320/p

Dimensions: 320mm x 245mm x 380mm

Net weight: 12.7776kg Gross weight: 13.2kg

PRODUCT OUTLINE



PALLET EXAMPLE

Height:

Width: 120cm (std Euro pallet)

Mepth: 80cm (std Euro pallet)

Cartons per pallet: 44carton/pallet

Cartons per row:

Net weight: 562.2144kg Gross weight: 580.8kg

Datasheet and description



Avide LED Flood Light Slim 10W CW 6400K

Product code: ABSFLCW-10W

Brand link: avidelighting.com/qr/ABSFLCW-10W

ID: AB-190518

Company name: Armin Trade Kft.

Company address: Kossuth utca 22 2/4, 4024 Debrecen



Date of issue: 2023-11-15

Page: 3/3

PRODUCT DESCRIPTION

The battery-operated Avide COB LED floodlights enable portable, mobile use. Brightness is adjustable in two stages. They can provide the same brightness as traditional halogen floodlights but with much lower power consumption; thus when operated from a battery, they can ensure a longer operating time. The battery of the floodlight can be fully charged in 3 hours and with one full charge it can operate for up to 5 hours. COB (chip-on-board) represents one of the most recent LED technologies, focusing the emitted light much better and thus providing better lighting at a longer distance. LED floodlights can provide up to 20 times longer lifetime compared to products using traditional light bulbs. Due to its IP65 classification, it is perfectly suitable for both indoor and outdoor use. The edge of the floodlight features a metal frame that makes it possible to be turned and tilted, thus enabling you to adjust the adequate lighting angle.

The LED floodlights are sold with a 30 cm long cable end and the plug is not included in the package! The product may only be installed by a professional! Any operation with the power on carries the hazard of an electric shock.

The Avide COB Floodlights are available in neutral white (NW) / cold white (CW) color temperatures in 10W / 20W / 30W / 50W / 80W / 100W / 150W power output versions. The "SLIM" design is also available in neutral white (NW) / cold white (CW) color temperatures and a 10W / 20W / 30W / 50W power output.