

Avide LED Flood Light Industrial SMD 50W NW 4000K 160lm/W

Product code: AILFLNW-50W
Brand link:
ID: AB-190518
Company name: Bramcke Hungary Kft.
Company address: Kishatár utca 17., 4031 Debrecen

QR code:
Date of issue: 2024-05-11
Page: 1/3

SPECIFICATIONS

EAN code: 5999097954585
Warranty: 5year(s)
Working temperature:
Packaging: 1/b 20/c 640/p
Certifications: CE

TECHNICAL DETAILS

Wattage: 50W
Voltage: 175-265V
Beam angle: 120°
Dimmability: No
Lumen output: 8 000lm
Color temperature: 4 000K
Lifetime: 50 000h
Energy class: C
Type of LED: SMD
Driver: IC
CRI: 80
IP standard: IP65

BOX PICTURE



Avide LED Flood Light Industrial SMD 50W NW 4000K 160lm/W

Product code:	AILFLNW-50W	QR code:	
Brand link:		Date of issue:	2024-05-11
ID:	AB-190518		
Company name:	Bramcke Hungary Kft.		
Company address:	Kishatár utca 17., 4031 Debrecen	Page:	2/3

PRODUCT SIZE

Width:	155mm
Height:	182mm
Depth:	36mm

CARDBOARD BOX

EAN:	5999097954585
Packaging:	1/b 20/c 640/p
Dimensions:	
Net weight:	619.5g
Gross weight:	640g

CARTON

EAN:	
Packaging:	1/b 20/c 640/p
Dimensions:	
Net weight:	12.3904kg
Gross weight:	12.8kg


PALLET EXAMPLE

Height:	
Width:	120cm (std Euro pallet)
Mepth:	80cm (std Euro pallet)
Cartons per pallet:	32carton/pallet
Cartons per row:	
Net weight:	396.4928kg
Gross weight:	409.6kg

PRODUCT PICTURE



PRODUCT OUTLINE



Avide LED Flood Light Industrial SMD 50W NW 4000K 160lm/W

Product code: AILFLNW-50W

Brand link:

QR code:

ID: AB-190518

Date of issue: 2024-05-11

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen

Page: 3/3

PRODUCT DESCRIPTION

The Avide SMD LED floodlights can provide the same brightness as traditional halogen lights but with a much lower power consumption, thus significant savings can be realized with their use. LED floodlights provide up to 20 times longer lifetime compared to products using traditional light bulbs. With their IP65 classification, they are also perfectly suitable for outdoor use. The edge of the floodlight features a movable metal frame, thus you can fix it on the ground, the wall or even the ceiling. After mounting, the angle can be adjusted anytime, thus it will provide the light you need exactly where you need it.

The LED floodlights are sold with a 30 cm long cable end and the plug is not included in the package! The product may only be installed by a professional! Any operation with the power on carries the hazard of an electric shock.

The Avide SMD floodlights are available in neutral white (NW) / cold white (CW) color temperatures in 10W / 20W / 30W / 50W power output versions, as well as in a neutral white (NW) color temperature and a 100W / 150W / 200W power output.