Datasheet and description



Avide LED Flood Light Slim SMD 30W with Stand 1.5m NW 4000K

Product code: ABSSTFLNW-30W

Brand link: avidelighting.com/qr/ABSSTFLNW-30W

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-05-05

Page: 1/3

SPECIFICATIONS

EAN code: 5999097919348

Warranty: 3year(s)
Working temperature: -20 - +50°C
Packaging: $1/b \ 10/c \ 360/p$

Certifications: CE

TECHNICAL DETAILS

Wattage: 30W

Voltage: AC180-240V

Beam angle: 120° Dimmability: No

Lumen output: 3 000lm
Color temperature: 4 000K
Lifetime: 30 000h

Energy class: F
Type of LED: SMD

Driver:

CRI: >70
IP standard: IP65

BOX PICTURE



Datasheet and description



Avide LED Flood Light Slim SMD 30W with Stand 1.5m NW 4000K

Product code: ABSSTFLNW-30W

Brand link: avidelighting.com/qr/ABSSTFLNW-30W

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-05-05

Page: 2/3

PRODUCT SIZE

Width: 211mm Height: 271mm Depth: 120mm

CARDBOARD BOX

EAN: 5999097919348 Packaging: 1/b 10/c 360/p

Dimensions: 220mm x 230mm x 75mm

Net weight: 822.8g Gross weight: 850g

PRODUCT PICTURE



PRODUCT OUTLINE

CARTON

EAN: 5999097919355 Packaging: 1/b 10/c 360/p

Dimensions: 395mm x 445mm x 245mm

Net weight: 8.228kg
Gross weight: 8.5kg

PALLET EXAMPLE

Height:

Width: 120cm (std Euro pallet)
Mepth: 80cm (std Euro pallet)

Cartons per pallet: 36carton/pallet

Cartons per row:

Net weight: 296.208kg
Gross weight: 306kg

Datasheet and description



Avide LED Flood Light Slim SMD 30W with Stand 1.5m NW 4000K

Product code: ABSSTFLNW-30W

Brand link: avidelighting.com/qr/ABSSTFLNW-30W

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-05-05

Page: 3/3

PRODUCT DESCRIPTION

Light your work area with the Avide SMD portable LED floodlights. LED floodlights can provide up to 20 times longer lifetime compared to products using traditional light bulbs. Due to its IP65 classification, it is perfectly suitable for both indoor and outdoor use. The edge of the floodlight features a metal frame that makes it possible to be turned and tilted, thus enabling you to adjust the adequate lighting angle.

Do not look directly into the floodlight! Do not use the fixture under water!

Due to its portability, you can take it where an extra light source is needed the most. The 3G0.75 type and 1.5meter-long power cable provides convenient access to the power source.

The Avide SMD Floodlights are available in a neutral white (NW) color temperature and 10W, 20W, 30W and 50W power output versions.